

SAFETY DATA SHEET

Product: PROPANO ESPECIAL

Revision: 01 Date: 06/13/2024 Pages: 1/8

1 - IDENTIFICATION

GHS Product identifier: PROPANO ESPECIAL

Other means of PRO613

identification:

Recommended use of Used in residential natural gas, cooking gas, in car engines and propellants for aerosol sprays.

the chemical:

Specific restrictions on There are not known restrictions on use.

use:

Supplier's details: Acelen

Address: ROD BA 523, KM 4, MATARIPE, CEP: 43900-000 - BA - Brasil.

Phone number: (71) 3511-8000 / (11) 5225-8900

Emergency phone

number:

EMERGENCIall: 0800 729 2756 / (11) 94759-7282 (Whatsapp) (24h)

2 - HAZARD IDENTIFICATION

Classification of the Flammable gases - Category 1A; substance or mixture: Gases Under Pressure - Liquefied;

Specific Target Organ Toxicity – Single Exposure - Category 3 - Narcotic.

Classification system

adopted:

Globally Harmonized System of Classification and Labeling of Chemicals (GHS), United Nations.

GHS label elements, including precautionary statements

Pictograms:







Signal word: DANGER

Hazard statement(s): H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H336 May cause drowsiness or dizziness.

Precautionary **PREVENTION**:

statement(s): P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P222 Do not allow contact with air.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, protective clothing, eye protection, face protection and hearing

protection.

RESPONSE TO EMERGENCY:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P319 Get medical help if you feel unwell.

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 In case of leakage, eliminate all ignition sources.

STORAGE:

P403 Store in a well-ventilated place.



SAFETY DATA SHEET

Product: PROPANO ESPECIAL

Pages: 2/8 Revision: 01 Date: 06/13/2024

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

DISPOSITION:

P501 Dispose of contents and container in accordance with local regulations.

Other hazards which do not result in

Simple asphyxiant. Forms explosive mixtures in contact with air.

3 - COMPOSITION/INFORMATION ON INGREDIENTS

Propane.

SUBSTANCE

classification:

Common chemical

name:

hazard:

Common name(s), synonym(s) of the

substance: CAS: 74-98-6

Components contributing to the Propylene (CAS 115-07-1): 1 - 5 %.

4 - FIRST-AID MEASURES

Description of necessary first-aid measures

Inhalation: Gases may cause dizziness and asphyxia. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Monitor respiratory function. If the victim shows difficulty breathing, then

give oxygen. If necessary, apply artificial respiration. Consult a doctor. Bring this SDS.

In case of contact of the product in pressurized form with the skin, it can cause injury or frostbite Skin:

(frostbite). Wash exposed skin immediately with sufficient amount of water. Clothing adhered to the skin should be thawed in warm water before being removed. Consult a doctor. Bring this SDS.

In case of contact of the product in pressurized form with eyes, may occur injury or frostbite. Wash Eye:

the eyes with sufficient amount of water immediately, keeping the eyes opened. In case of use of

contact lenses, remove them, if possible. Keep washing. Contact a doctor. Bring this SDS.

Ingestion: Not applicable.

Most important symptoms/effects, acute and delayed:

Contact of the liquefied gas with the skin can cause "freeze burns" (frostbite). Contact of the liquefied gas with the skin can cause "freeze burns" (frostbite). May cause drowsiness or dizziness,

may cause dizziness and nausea.

Indication of immediate medical attention and special treatment needed, if necessary:

Avoid contact with the product to help the victim. Keep victim warm and quiet. Symptomatic treatment should comprise mainly supportive measures such as correction of electrolyte disturbances, metabolic, and respiratory support. In case of skin contact do not rub the affected

5 - FIRE-FIGHTING MEASURES

Extinguishing media: Appropriate: carbon dioxide (CO₂), water mist and powder.

Inappropriate: water jet directly.

Specific hazards arising from the chemical:

The combustion of the chemical containers may form toxic and irritant gases such as carbon monoxide and carbon dioxide.



SAFETY DATA SHEET

Product: PROPANO ESPECIAL

Revision: 01	Date: 06/13/2024	Pages: 3/8
	Gases may be heavier than air and may accumulate in low or confined areas, such basements. Containers may explode if heated.	n as sewers and
Special protective actions for fire-fighters:	Use self-contained breathing apparatus (SCBA) operated in positive pressure mode protective clothing. Containers and tanks involved in the fire should be cooled with w	•

6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel:	Prevent sparks or flames. Do not smoke. Do not touch damaged containers or spilled material without the use of appropriate clothing. Avoid exposure to the product. Stay in a safe place, with wind from behind. Use personal protective equipment as described in Section 8.
For emergency responders:	Wear complete PPE with safety glasses, safety gloves, suitable protective clothing and closed shoes. In case of leakage, where exposure is high, it is recommended to use a suitable respiratory protection mask.
Environmental precautions:	Avoid that the dispersed gas reaches waterways or sewage system.
Methods and materials for containment and cleaning up:	Release the contents slowly into the atmosphere. Stay downwind. Do not pour water directly into the leak point. Due to the product dispersion in the environment, it is recommended that the area is ventilated until the release site. For final destination, proceed pursuant to Section 13 of this SDS.

7 - HANDLING AND STORAGE

Precautions	for sa	afe ha	andling
--------------------	--------	--------	---------

Precautions for safe handling:

Handle in a well ventilated area or with general system of ventilation/local exhaust. Avoid gases and aerosols formation. Avoid exposure to the chemical, since the effects may not be felt immediately.

Avoid contact with incompatible materials.

General hygiene:

Wash hands and face thoroughly after handling and before eating, drinking, smoking or going to the bathroom. Contaminated clothing should be changed and washed before reuse. Remove clothing and protective equipment contaminated before entering eating areas.

Conditions for safe storage, including any incompatibilities

Technical measures for prevention of fire and explosion:

Keep away from heat, sparks, open flames and hot surfaces. - Do not smoke. Keep container tightly closed. Ground the container vessel and the receiver of the product during transfers. Only use antisparking tools. Avoid the accumulation of electrostatic charges. Use electrical equipment, ventilation and lighting explosion proof. Use personal protective equipment as described in Section 8.

Conditions for safe storage, including any incompatibilities:

Store in a well ventilated place, away from sunlight. Keep container closed. Keep away from high temperatures and ignition sources.

It is not necessary addition of stabilizers and antioxidants to ensure the durability.

This material may react dangerously with some incompatible materials as outlined in Section 10.

Keep away from incompatible materials.

Packaging compatibilities:

Similar to the original packaging.

Inadequate packaging

There are not known unsuitable material.

materials:

8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational exposure limit:

The values below apply to workplaces.

- Propane:



SAFETY DATA SHEET

Product: PROPANO ESPECIAL

Revision: 01 Date: 06/13/2024 Pages: 4/8

OSHA - PEL - TWA: 1000 ppm (1800 mg/m³) (29 CFR 1910.1000 Table Z-1) (CFR);

NIOSH - REL - TWA: 1000 ppm (1800 mg/m³);

ACGIH - TLV - TWA: (D. EX) (AF).

- Propylene:

ACGIH - TLV - TWA: 500 ppm.

D: Simple asphyxiant;

EX: Explosion hazard: the substance is a flammable asphyxiant or excursions above the TLV® could

approach 10% of the lower explosive limit; AF: See Appendix F: Minimal Oxygen Content. CFR: See mentioned item in OSHA CFR.

Biological limit: Not established.

Other limits and values: Not established.

Appropriate engineering

controls:

Promote mechanical ventilation and exhaust system to outside. These acts help reducing the exposition to the product. It is recommended to make emergency showers and eye wash facilities available in the work area. Maintain airborne concentrations of the substance or mixture below stated occupational exposure limits. Maintain atmospheric concentrations of the constituents of the material below occupational exposure limits indicated.

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection: Wide-view glasses with splash protection.

Skin protection: Safety shoes and safety clothing to protect the whole body from chemical splashes. Protective

gloves against chemicals such as PVC.

Respiratory protection: Use of respirator with filter against vapors and organic mists is recommended for average exposures

above half the TLV-TWA. In cases where exposure exceeds 3 times the TLV-TWA value, use a self-contained, full facepiece, air-supplied respirator (SCBA) operated in positive pressure mode. Follow guidance from the Respiratory Protection Program (PPR), 4th ed. São Paulo: Fundacentro, 2016.

Thermal hazards: It does not present thermal hazards.

9 - PHYSICAL AND CHEMICAL PROPERTIES

Aspect: Gas.

Color: Colorless.

Odour: Characteristic.

Melting point/freezing

point:

-188 °C (-306.4 °F).

Boiling point or initial boiling point and boiling

-42 °C (-43.6 °F).

boiling point and boiling range:

Flammable.

Lower and upper explosion

Flammability:

Upper: 9.5 % and Lower: 2.3 %.

limit/flammability limit:

Not applicable.

Flash point:
Auto-ignition

450 °C (842 °F).

temperature:



SAFETY DATA SHEET

Product: PROPANO ESPECIAL

Revision: 01 Date: 06/13/2024 Pages: 5/8

Decomposition

temperature:

Not available. Not applicable.

pH: Kinematic viscosity: Not available.

Solubility(ies): Miscible in water (50 to 500 g/L). Soluble in ether.

Partition coeficient n-

Not available.

octanol/water (log value):

Vapour pressure:

15 kgf/cm² (1470997.5 Pa) at 37.8 °C (100.04 °F).

Relative vapour density: 1.56 (air = 1).

Density and/or relative

density:

Relative density: 0.493 (water at 4 °C(39,2 °F) = 1).

Particle characteristics: Not applicable.

Other information: Not applicable.

10 - STABILITY AND REACTIVITY

Reactivity: Reactivity is not to be expected under normal conditions of temperature and pressure.

Chemical stability: Stable product under normal conditions of temperature and pressure.

Possibility of hazardous

Propane: May react dangerously with risk of explosion in contact with chlorine dioxide. May react

reactions: dangerously in contact with barium peroxide.

Conditions to avoid:

Elevated temperatures. Ignition sources. Contact with incompatible materials.

Incompatible material: Acetylene, barium peroxide, bromine, chloro dioxide, nitrogen oxides, oxidizing agents and oxygen.

Hazardous decomposition products:

In combustion it releases anesthetic vapours, monoxide and carbon dioxide.

11 - TOXICOLOGICAL INFORMATION

Acute toxicity: Product not classified as acute toxic by inhalation.

ATEmix Gases (4h): > 20000 μ L/L (ppm).

Skin corrosion/irritation: Contact of the liquefied gas with the skin can cause "freeze burns" (frostbite).

Serious eye

damage/irritation:

Contact of the liquefied gas with the skin can cause "freeze burns" (frostbite).

Respiratory or skin sensitization:

It is not expected to present respiratory or skin sensitization.

Germ cell mutagenicity: It is not expected to show mutagenicity in germ cells.

Carcinogenicity: It is not expected to be carcinogenic.

Reproductive toxicity: It is not expected to be reproductively toxic.

STOT - Single

May cause drowsiness or dizziness, may cause dizziness and nausea.

exposure:

STOT - Repeated It is not expected to exhibit specific target organ toxicity on repeated exposure.



SAFETY DATA SHEET

Product: PROPANO ESPECIAL

Revision: 01 Date: 06/13/2024 Pages: 6/8

exposure:

Aspiration hazard: It is not expected to present an aspiration hazard.

12 - ECOLOGICAL INFORMATION

Toxicity: It is not expected to be ecotoxic.

Persistence and

It is not expected to present persistence and degradability.

degradability:

Bioaccumulative

potential:

Presents low bioacumulative potencial in aquatic organisms. Information regarding to:

Propane:

BCF: 13 (calculated) log Kow: 2.36 - Propylene: BCF: 5 (calculated) $\log K_{\rm ow}$: 1.77.

Mobility in soil: Not determined.

Other adverse effects: No other environmental effects known.

13 - DISPOSAL CONSIDERATIONS

Disposal methods

Must be disposed of as hazardous waste in compliance with local regulations. The treatment and disposal should be evaluated for each specific product.

Keep the product remains in its original and properly closed containers. Disposal should be performed as established for the product.

14 - TRANSPORT INFORMATION

Road: UN - United Nations: Model Regulations:

· Recommendations on the Transport of Dangerous Goods.

UN number: 1978

Proper shipping name: **PROPANE**

Primary risk class or

division:

2.1

Subsidiary risk class or

division:

NA

Packing group: NA

Environmental hazards: The product is not considered dangerous for the environment for land transport.

Railway regulations: COTIF - Convention concerning International Carriage by Rail:

• Appendix C: RID - Regulations concerning the International Carriage of Dangerous Goods

by Rail.

1978 UN number:

Proper shipping name: **PROPANE**

2.1 Primary risk class or



SAFETY DATA SHEET

Product: PROPANO ESPECIAL

Pages: 7/8 Revision: 01 Date: 06/13/2024 division: Subsidiary risk class or NA division: NA Packing group: Environmental hazards: The product is not considered dangerous for the environment in rail transport. Sea: IMO - International Maritime Organization: • IMDG Code - International Maritime Dangerous Goods Code. 1978 UN number: **PROPANE** Proper shipping name: Primary risk class or 2.1 division: Subsidiary risk class or NA division: Packing group: NA Environmental hazards: It's not considered a marine pollutant for transportation. EmS: F-D,S-U Air: IATA - International Air Transport Association: · DGR - Dangerous Goods Regulation. UN number: 1978 Special precautions for Not applicable. user: Maritime transport in Consult regulations: bulk according to IMO instruments: International Maritime Organization: MARPOL: Articles, protocols, annexes, unified interpretations of the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocol of 1978 relating thereto, consolidated edition. IMO, London, 2006; · International Maritime Organization: IBC code: International code for the construction and equipment of shipping carrying dangerous chemicals in bulk: With Standards and guidelines relevant

15 - REGULATORY INFORMATION

Convention concerning Safety in the use of Chemicals at Work (Convention 170) - International Labour Organization, 1990.

to the code. IMO, London, 2007.

16 - OTHER INFORMATION

This SDS was prepared based on current knowledge about the proper product handling and under normal conditions of use, in accordance with the application specified on the packaging. Any other use of the product involving their combination with other materials, and use various forms of those indicated, are the responsibility of the user. Warns that the handling of any chemical substance requires the prior knowledge of its hazards for the user. In the workplace it is for the user company's product promotes training of its collaborators about the possible risks arising from exposure to the chemical.

Change control:



SAFETY DATA SHEET

Product: PROPANO ESPECIAL

Revision: 01 Date: 06/13/2024 Pages: 8/8

Version	Manufacture date	Changes
01	03/20/2023	Elaboration

Abbreviations:

ACGIH - American Conference of Governmental Industrial Hygienists;

ATEmix - Acute Toxicity Estimate of the mixture;

BCF - Bioconcentration factor;

CAS - Chemical Abstracts Service;

Kow - Octanol-water partition coefficient;

NIOSH - National Institute for Occupational Safety and Health;

OSHA - Occupational Safety & Health Administration;

PEL - Permissible Exposure Limit;

REL - Recommended Exposure Limit;

TLV - Threshold Limit Value;

TWA - Time Weighted Average;

UN - United Nations.

Bibliographic references:

ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIALS HYGIENISTS. TLVs® and BEIs®: Based on the Documentation of the Threshold Limit Values (TLVs®) for Chemical Substances and Physical Agents & Biological Exposure Indices (BEIs®). Cincinnati-USA, 2023.

GHS - GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS. 10th rev. ed. New York and Geneva: United Nations, 2023.